

KARTT®

TRAILER PARTS



KARTT
Orange
Premium jockey wheels

A company that specialises in jockey wheels
with superb quality, remarkable performance & unrivaled choice



www.kartt.co.uk

KARTT Orange

Premium jockey wheels

Kartt is a UK company with production workshops and warehousing base in Bedford, England and is a major supplier to the trailer industry.

Our mission is to supply a high quality product which incorporates quality, performance and innovation.

Why use Kartt Orange premium jockey wheels?

1 High visibility orange wheels

One major reason for damaged jockey wheels is not being wound up once hitched to the towing vehicle. On tests Kartt found that a forgotten lowered orange wheel could be easier to see from a distance, when the driver makes their final visible check before driving off.

2 Load tested to twice working capacity.

Kartt jockey wheels are tested to twice recommended working capacity to make sure that there is a big safety factor.

3 Full roller bearings

Higher quality roller bearings are used in the winding mechanism that give a smoother and trouble free performance.

4 High quality tube

Kartt uses a high quality bright steel tube for the core and outside body of the jockey wheel. This is also thicker than many other jockey wheels that are available.

5 Quality of electro plating

Kartt uses a greater thickness of plating to a higher standard of specification.

6 Heavy duty wheel holder

Nearly all of the Kartt Orange wheel holders are very heavy duty and are made from 6mm steel, formed in specially designed tooling to give the maximum amount of structural strength.

7 Ergonomically design knob

Specially designed to give simple and firm grip even with wet hands or a greasy glove.

8 Forged steel handle

Much stronger than other steel handles

9 Powder coated rim

This colour is baked onto the metal rim using a quality powder paint that gives a far higher resistance to the day-to-day elements such as mud, road salt and sea water.

10 Quality welding

All welding is completed to a strict quality control system

11 High resistant bearings

Kartt orange uses special nylon bearings that give the maximum amount of resistance for heavy loads and wear. They also form a permanent gap between the wheel and the holder so that there is no metal to metal rubbing.

12 Heavy duty steel rim

Nearly all the Kartt orange wheels have a 2mm steel rim, nearly twice the thickness of other cheaper jockey wheels available.

13 Higher quality rubber tyre


The rubber used in the Kartt Orange range has a higher content of pure rubber and is constantly load and temperature tested.



63 Murdock Road, Manton Lane Industrial Estate, Bedford MK41 7PL


www.kartt.co.uk

PLASTIC RIM




Part no	KJW4801
Tube size	ø48 mm
Rim	plastic
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	4.81 kg
Spare wheel	KW005

PNEUMATIC




Part no	KJW4802
Tube size	ø48 mm
Rim	steel
Tyre	pneumatic
Wheel ø	260 x 85 mm
Length ext	220 mm
Max Nose wgt	100 kg
Item wgt	4.68 kg
Spare wheel	KW004

STEEL RIM LOW HANDLE




Part no	KJW4803
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	4.82 kg
Spare wheel	KW006

STEEL RIM HIGH HANDLE



Part no	KJW4803H
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	4.82 kg
Spare wheel	KW006


EXTRA TALL



Part no	KJW4803T
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.3 kg
Spare wheel	KW006


JOCKEY WHEELS 48mm ø heavy duty

RIBBED




Part no	KJW4804
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.01 kg
Spare wheel	KW008

RIBBED HEAVY DUTY




Part no	KJW4804D
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	230 mm
Max Nose wgt	350 kg
Item wgt	9.01 kg
Spare wheel	KW011R

RIBBED AUTO LIFT



Part no	KJW4806
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	211+165 mm
Max Nose wgt	250 kg
Item wgt	9.46 kg
Spare wheel	KW008


RIBBED AUTO LIFT HEAVY DUTY



Part no	KJW4806D
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	211+165 mm
Max Nose wgt	250 kg
Item wgt	9.46 kg
Spare wheel	KW011R


JOCKEY WHEELS 48mm ø heavy duty

SMOOTH




Part no	KJW4805
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	250 kg
Item wgt	9.01 kg
Spare wheel	KW008

SMOOTH HEAVY DUTY




Part no	KJW4805D
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.01 kg
Spare wheel	KW011R

SMOOTH AUTO LIFT




Part no	KJW4807
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	211+165 mm
Max Nose wgt	250 kg
Item wgt	9.46 kg
Spare wheel	KW008

SMOOTH AUTO LIFT HEAVY DUTY




Part no	KJW4807D
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	211+165 mm
Max Nose wgt	250 kg
Item wgt	9.46 kg
Spare wheel	KW011R

60mm HEAVY DUTY SMOOTH




Part no	KJW6001
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	350 mm
Max Nose wgt	300 kg
Item wgt	7.95 kg
Spare wheel	CW601

60mm AUTO LIFT WIDE WHEEL




Part no	KJW6005
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	245+245 mm
Max Nose wgt	400 kg
Item wgt	12.37 kg
Spare wheel	CW601

60mm AUTO LIFT



Part no	KJW6006
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	250+200 mm
Max Nose wgt	250 kg
Item wgt	9.86 kg
Spare wheel	CW008

60mm SQUARE BODY




Part no	KJW6010
Tube size	60 X 60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	250+200 mm
Max Nose wgt	250 kg
Item wgt	10.21 kg
Spare wheel	CW008

NEW Kartt TURN-LOK

Turn-Lok is a special system incorporated in our Turn-Lok jockey wheels that helps prevent the handle unwinding when travelling. This eliminates the use of clips, chains or rubber bands that an operator can forget to fix or can become damaged and stops the jockey wheel falling onto the road.


The Turn-Lok works automatically without the operator having to remember any additional operations other than when using a standard jockey wheel.

43mm TURN-LOK




Part no	KJW43L
Tube size	ø43 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	165 mm
Max Nose wgt	150 kg
Item wgt	5.1 kg
Spare wheel	KW006

48mm TURN-LOK




Part no	KJW4803L
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.5 kg
Spare wheel	KW006

RIBBED TURN-LOK



Part no	KJW4804L
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.01 kg
Spare wheel	KW008


SMOOTH TURN LOK



Part no	KJW4805L
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	250 kg
Item wgt	9.01 kg
Spare wheel	KW008

35mm CLAMP FOR PROPSTANDS


Designed to ensure jockey wheels stay in place under the toughest conditions.



Part no	KCL3501
Tube size	ø 35 mm
Material	steel
Bolt holes centre	105 mm
Fixing holes	2
Item wgt	0.78kg

48mm DIAMETER CLAMP


Designed to ensure jockey wheels stay in place under the toughest conditions.



Part no	KCL4801
Tube size	ø 48 mm
Material	steel
Bolt holes centre	105 mm
Fixing holes	2
Item wgt	0.76kg

48 mm DIAMETER CLAMP + CAST BASE


A cast base to help further strengthen the clamp.



Part no	KCL4802
Tube size	ø 48 mm
Material	steel + CI
Bolt holes centre	105 mm
Fixing holes	6
Item wgt	0.96 kg

60mm DIAMETER CLAMP

Suitable for all 60 mm Heavy Duty Jockey Wheels where keeping heavy loads safe and secure is a must.



Part no	KCL6001
Tube size	ø 60 mm
Material	steel
Bolt holes centre	105 mm
Fixing holes	10
Item wgt	1.56 kg

REPLACEMENT WHEELS FOR THE KARTT ORANGE PREMIUM JOCKEY WHEEL RANGE

WHEELS



Heavy duty low profile

Part no	KW011R
Nominal wheel ø	200x50 mm
Rim	Powder coated steel
Tyre	solid rubber

Plastic wheel

Part no	KW005
Nominal wheel ø	200x50 mm
Rim	plastic
Tyre	solid rubber

Standard wheel

Part no	KW008
Nominal wheel ø	200x56 mm
Rim	Powder coated steel
Tyre	solid rubber

Pneumatic wheel

Part no	KW004
Nominal wheel ø	260x85 mm
Rim	Powder coated steel
Tyre	pneumatic

Basic wheel

Part no	KW006
Nominal wheel ø	200x50 mm
Rim	Powder coated steel
Tyre	solid rubber

Extra wide wheel


Part no	CW601
Nominal wheel ø	220x65 mm
Rim	galvanised steel
Tyre	solid rubber

All Kartt orange jockey wheels use tyres that have a higher content of pure rubber and the rims are made of considerably thicker steel than conventionally used. They are constantly load and pressure tested to make sure that they will continue to operate under today's ever changing extreme conditions.




COMMERCIAL 43mm to 48mm JOCKEY WHEELS

43mm TURN-LOK




Part no	C43L
Tube size	43 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	165 mm
Max Nose wgt	150 kg
Item wgt	5.3 kg
Spare wheel	CW006

48mm PNEUMATIC WHEEL




Part no	C482
Tube size	ø48 mm
Rim	steel
Tyre	pneumatic
Wheel ø	260 x 85 mm
Length ext	220 mm
Max Nose wgt	100 kg
Item wgt	5.2 kg
Spare wheel	CW015

48mm HIGH HANDLE



Part no	C483H
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.3 kg
Spare wheel	CW006

48mm HEAVY DUTY RIBBED




Part no	C484
Tube size	48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.1 kg
Spare wheel	CW008

48mm HEAVY DUTY SMOOTH




Part no	C485
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	230 mm
Max Nose wgt	250 kg
Item wgt	9.0 kg
Spare wheel	CW008

48mm PLASTIC WHEEL




Part no	C481
Tube size	ø48 mm
Rim	plastic
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.2 kg
Spare wheel	CW014

48mm SOLID WHEEL




Part no	C483
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.3 kg
Spare wheel	CW006

48mm EXTRA TALL




Part no	C483T
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 50 mm
Length ext	220 mm
Max Nose wgt	150 kg
Item wgt	5.5 kg
Spare wheel	CW006

48mm HEAVY DUTY RIBBED (Wide Wheel)




Part no	C484W
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.1 kg
Spare wheel	CW601

48mm HEAVY DUTY SMOOTH (Wide Wheel)




Part no	C485W
Tube size	ø48 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	230 mm
Max Nose wgt	300 kg
Item wgt	9.2 kg
Spare wheel	CW601

60mm PLAIN



Part no	C61
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	350 mm
Max Nose wgt	300 kg
Item wgt	8.3 kg
Spare wheel	CW601

60mm AUTO LIFT



Part no	C66
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	250+200 mm
Max Nose wgt	250 kg
Item wgt	9.86 kg
Spare wheel	CW008

48mm DIAMETER CLAMP




Part no	CL481
Tube size	ø48 mm
Material	steel
Bolt holes centre	105 mm
Fixing holes	2
Weight	0.76 kg

SPARE WHEELS




Part no	CW006
Wheel ø	200 x 50 mm
Part no	CW008
Size	200 x 56 mm
Part no	CW601
Size	220 x 65 mm

PT80SQ 210




60mm HEAVY DUTY AUTO LIFT



Part no	C65
Tube size	ø60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	220 x 65 mm
Length ext	245+245 mm
Max Nose wgt	400 kg
Item wgt	12.37 kg
Spare wheel	CW601

60mm SQUARE AUTO LIFT



Part no	C610
Tube size	60 x 60 mm
Rim	steel
Tyre	solid rubber
Wheel ø	200 x 56 mm
Length ext	250+200 mm
Max Nose wgt	250 kg
Item wgt	10.21 kg
Spare wheel	CW008

60mm DIAMETER CLAMP



Part no	CL601
Tube size	ø60 mm
Material	steel
Bolt holes centre	105 mm
Fixing holes	10
Weight	1.56 kg


STATIC PROPSTANDS



Available in ø34 mm and ø48 mm in different sizes to suit the majority of needs.

34 mm x 450 mm	Part No P3445
34 mm x 600 mm	Part No P3460
34 mm x 750 mm	Part No P3475
48 mm x 600 mm	Part No P4860
48 mm x 750 mm	Part No P4875

PT80SQ 280



A quick look at the range

Part No.	Specification	Tube Size	Length ext	Max Nose wgt	Item wgt	Spare Wheel
KARTT ORANGE PREMIUM JOCKEY WHEELS						
KJW43L	43 mm Turn-Lok	Ø43 mm	165 mm	150kg	5.1kg	KW006
KJW4801	Plastic Rim	Ø48 mm	220 mm	150kg	4.81kg	KW005
KJW802	Pneumatic	Ø48 mm	220 mm	100kg	4.68kg	KW004
KJW803	Steel Rim Low Handle	Ø48 mm	220 mm	150kg	4.82kg	KW006
KJW4803H	Steel Rim High Handle	Ø48 mm	220 mm	150kg	4.82kg	KW006
KJW4803T	48 mm Extra Tall	Ø48 mm	220 mm	150kg	5.3kg	KW006
KJW4803L	48 mm Turn-Lok	Ø48 mm	220 mm	150kg	5.5kg	KW006
KJW4804	Ribbed	Ø48 mm	230 mm	300kg	9.01kg	KW008
KJW4804D	Ribbed Heavy Duty	Ø48 mm	230 mm	350kg	9.01kg	KW011R
KJW4804L	Ribbed Turn-Lok	Ø48 mm	230 mm	300kg	9.01kg	KW008
KJW4806	Ribbed Auto Lift	Ø48 mm	221+165mm	250kg	9.46kg	KW008
KJW4806D	Ribbed Auto Lift Heavy Duty	Ø48 mm	221+165mm	250kg	9.46kg	KW011R
KJW4805	Smooth	Ø48 mm	230 mm	250kg	9.01kg	KW008
KJW4805D	Smooth Heavy Duty	Ø48 mm	230 mm	300kg	9.01kg	KW011R
KJW4805L	Smooth Turn Lok	Ø48 mm	230 mm	300kg	9.01kg	KW008
KJW4807	Smooth Auto Lift	Ø48 mm	221+165mm	250kg	9.46kg	KW008
KJW4807D	Smooth AutoLift Heavy Duty	Ø48 mm	221+165mm	250kg	9.46kg	KW011R
KJW6001	60 mm Heavy Duty Smooth	Ø60 mm	350 mm	300kg	7.95kg	CW601
KJW6005	60 mm Auto Lift Wide Wheel	Ø60 mm	245+245mm	400kg	12.37kg	CW601
KJW6006	60 mm Auto Lift	Ø60 mm	250+200mm	250kg	9.86kg	CW008
KJW6010	60 mm Square Body	Ø60 mm	250+200mm	250kg	10.21kg	CW008
COMMERCIAL JOCKEY WHEELS						
C43L	43 mm Turn-Lok	Ø43 mm	165 mm	150kg	5.3kg	CW006
C481	48 mm Plastic Wheel	Ø48 mm	220 mm	150kg	5.2kg	CW014
C482	48 mm Pneumatic Wheel	Ø48 mm	220 mm	100kg	4.68kg	CW015
C483	48 mm Solid Wheel	Ø48 mm	220 mm	150kg	5.3kg	CW006
C483H	48 mm High Handle	Ø48 mm	220 mm	150kg	5.3kg	CW006
C483T	48 mm Extra Tall	Ø48 mm	220 mm	150kg	5.5kg	CW006
C484	48mm Heavy Duty Ribbed	Ø48 mm	230 mm	300kg	9.1kg	CW008
C484W	48mm Ribbed Wide Wheel	Ø48 mm	230 mm	300kg	9.1kg	CW601
CW485	48 mm Heavy Duty Smooth	Ø48 mm	230 mm	250kg	9.0kg	CW008
CW485W	48 mm Smooth Wide Wheel	Ø48 mm	230 mm	300kg	9.2kg	CW601
C61	60 mm Plain	Ø60 mm	350 mm	300kg	8.3kg	CW601
C65	60 mm Heavy Duty Auto Lift	Ø60 mm	245+245mm	400kg	12.37kg	CW601
C66	60 mm Auto Lift	Ø60 mm	250+200mm	250kg	9.86	CW008
C610	60 mm Square	Ø60 mm	250+200mm	250kg	10.21kg	CW008



www.kartt.co.uk

All enquiries to sales@kartt.co.uk
or contact us through the website

63 Murdock Road, Manton Lane Industrial Estate, Bedford MK41 7PL

contact your nearest dealer for more information

all products are subject to change due to continued development 2018 rev1