

REDUCERS

The reducers are made to various sizes, lengths and wall thicknesses, complete with weld-on ends suitable for all connecting systems: grooved, metric, raised, male-female, etc.

Quality: E355 (ST 52), API 5L-B.

On request they can be hardened for a longer life. Some sizes can be made in double wall induction hardened steel. We can make any kind of reducer according to the customer specifications.

DN1 - DN2		Wall thick.		Length		Type	Code Number	Weld-on ends
in.	mm	in.	mm	in.	mm			

RC - Reducers

2" - 1.½"	50 - 38	0,218	5,54	15	381	RC 2015 381/55 20R-15R	4A210381DD	HD-HD
			0,218	5,54	39,370	1000	RC 2015 1000/55 20R-15R	4A211000DD
2.½" - 2"	65 - 50	0,279	7,1	19,685	500	RC 2520 500/71 25G-20G	4D250500AA	Grooved-Grooved
				27,992	711	RC 2520 711/71 25R-20R	4D250711DD	HD-HD
				32,047	814	RC 2520 814/71 25R-20R	4D250814DD	HD-HD
				39,370	1000	RC 2520 1000/71 25G-20G	4D251000AA	Grooved-Grooved
3" - 2"	75 - 50	0,279	7,1	15	381	RC 3020 381/71 30R-20R	4D320381DD	HD-HD
				19,685	500	RC 3020 500/71 30G-20G	4D320500AA	Grooved-Grooved
				27,992	711	RC 3020 711/71 30R-20R	4D320711DD	HD-HD
				32,047	814	RC 3020 814/71 30R-20R	4D320814DD	HD-HD
				35	889	RC 3020 889/71 30R-20R	4D320889DD	HD-HD
				39,370	1000	RC 3020 1000/71 30G-20G	4D321000AA	Grooved-Grooved
3" - 2.½"	75 - 65	0,279	7,1	19,685	500	RC 3025 500/71 30G-25G	4D330500AA	Grooved-Grooved
				32,047	814	RC 3025 814/71 30R-25R	4D330814DD	HD-HD
				35	889	RC 3025 889/71 30R-25R	4D330889DD	HD-HD
				39,370	1000	RC 3025 1000/71 30G-25G	4D331000AA	Grooved-Grooved
4" - 2"	100 - 50	0,248	6,3	19,685	500	RC 4020 500/63 45M-30G	4G420500CA	Metric-Grooved
				39,370	1000	RC 4020 1000/63 45M-30G	4G421000CA	Metric-Grooved
4" - 2.½"	100 - 65	0,248	6,3	19,685	500	RC 4025 500/63 45M-30G	4G410500CN	Metric-Grooved (3")
				39,370	1000	RC 4025 1000/63 45M-30G	4G411000CN	Metric-Grooved (3")
				59,055	1500	RC 4025 1500/63 45M-30G	4G411500CN	Metric-Grooved (3")
4" - 3"	100 - 75	0,248	6,3	12	305	RC 4030 305/63 40R-30R	4G430305DD	HD-HD
				19,685	500	RC 4030 500/63 45M-30G	4G430500CA	Metric-Grooved
				27,992	711	RC 4030 711/63 40R-30R	4G430711DD	HD-HD
				32,047	814	RC 4030 814/63 40R-30R	4G430814DD	HD-HD
				35	889	RC 4030 889/63 40R-30R	4G430889DD	HD-HD
				39,370	1000	RC 4030 1000/63 45M-30G	4G431000CA	Metric-Grooved
				59,055	1500	RC 4030 1500/63 45M-30G	4G431500CA	Metric-Grooved
4" - 3.15"	100 - 80	0,248	6,3	39,370	1000	RC 4034 1000/63 45M-34M	4G441000CC	Metric-Metric
4" - 3.35"	100 - 85	0,248	6,3	39,370	1000	RC 4035 1000/63 45M-45M	4G451000CC	Metric-Metric
5" - 2.½"	125 - 65	0,236	6,0	39,370	1000	RC 5025 1000/60 55M-30G	4J511000CN	Metric-Grooved (3")
5" - 3"	125 - 75	0,236	6,0	39,370	1000	RC 5030 1000/60 55M-30G	4J531000CA	Metric-Grooved
5" - 4"	125 - 100	0,236	6,0	19,685	500	RC 5040 500/60 55M-45M	4J540500CC	Metric-Metric
5" - 4"	125 - 100	0,236	6,0	39,370	1000	RC 5040 1000/60 55M-45M	4J541000CC	Metric-Metric

